

## PHD BY PUBLICATION

### The influence of minimum stress on the fatigue life of non strain-crystallising elastomers

Abraham, Frank

*Award date:*  
2002

*Awarding institution:*  
Coventry University  
Deutsches Institut für Kautschuktechnologie

[Link to publication](#)

#### **General rights**

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of this thesis for personal non-commercial research or study
- This thesis cannot be reproduced or quoted extensively from without first obtaining permission from the copyright holder(s)
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

#### **Take down policy**

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

## **List of Redactions Due to Third Party Copyright**

Page 6 Fig.1 Straining of elastomer molecules (diagrammatically)

Page 7 Fig.2 Typical force-extension curve for vulcanised rubber

Page 8 Fig.3 Stress-strain curve of an amorphous elastomer

Page 9 Fig.4 Rebound resilience as a function of temperature

Page 10 Fig.5 Effect of temperature on dynamic properties

Page 11 Fig.6 Dependency of Young's modulus  $E^*$  on the dynamic double strain amplitude for natural rubber vulcanisate containing various proportions of carbon black

Page 12 Fig.7 Dependency on the loss factor  $\tan\delta$  on the dynamic double strain amplitude for a natural rubber vulcanisate containing various proportions of carbon black

Page 13 Fig.8 A qualitative interpretation of the shear modulus, strain amplitude curves

Page 14 Fig.9 Effect of repeated stretching on load-extension curves of NR vulcanizate gum

Page 16 Fig.10 Schematic diagram showing slippage of chains attached to two filler particles

Page 17 Fig.11 Stress induced softening of a carbon black-filled vulcanised copolymer of styrene and butadiene

Page 18 Fig.12 Relationship between frequency of vibration and temperature at various frequencies for natural rubber

Page 19 Fig.13 Stress-strain-curve of different polymers

Page 20 Fig.14 Stress-strain-curve of a cured rubber – a: experimental; theoretical

Page 21 Fig.15 X-ray diagram showing different distances to the crack tip of a five times stretched NR-test specimen

Page 25 Fig.16 Crack growth test specimens

Page 27 Fig.17 Relationship between rate of crack growth,  $dc/dn$ , and tearing energy, 'T' for natural rubber

Page 28 Fig.18 Crack growth rate  $dc/dN$ , vs. tearing energy, T for unified NR in laboratory atmosphere at 1.67 Hz

Page 44 Fig.27 Principle sketch of the tear analyser

Page 45 Fig.28 Individual recording of stresses and strains

These figures have been removed due to third party copyright. The unabridged version of the thesis can be viewed at the Lanchester Library, Coventry University